

1500 V-MILL

OPTIONS

- Platform & leg package includes (6) legs, (2) sets of stairs, 3' wide catwalk on both sides of platform and handrails. Catwalk and handrails remove for transporting. With catwalks attached, overall size of platform is 14'7" wide and 17'6" long. Standard legs give platform an overall height of 85" high
- Longer legs
- Many infeed and outfeed options available. Please contact your Morbark sawmill specialist for more information.



SPECIFICATIONS Note: Specifications may vary with equipment options

03052010

GENERAL

Power Up to 1000 HP
 Hammers Thirty 2" thick steel fixed hammers with double-edged, replaceable teeth inserts
 Screens 1" thick wear form steel screens
 Hammermill opening 37" x 62"
 Rotor dimensions 23-1/2" diameter with six 2-1/2" hammer retaining rods mounted on a 8-1/4" diameter rotor shaft

STANDARD EQUIPMENT

37" x 62" Hammermill opening with heavy duty 23-1/2" diameter rotors. Sixteen 1-5/8" (2-piece) thick rotor plated keyed on an 8-1/4" diameter rotor shaft with 5-3/16" bearings, six 2-1/2" hammer retaining rods, Thirty 2-1/2" wide double-edged replaceable teeth inserts
 (1) set of three 5" hexagon x 1" thick wear form steel heavy duty grates
 Hammermill base with grate support
 Impact hopper is constructed of 1/2" steel. Hopper has AR plate bolt on wear plates. Hopper is hinged for easy access to hammermill and grates. Two hydraulic cylinders with safety lockouts operate Hopper tilt.

110 volt power pack to open hopper is furnished when no hydraulic pump stand is ordered
 The frame supporting the hammermill is made of 12" x 8" structural tubing and is 8'7" wide and 17'6" (single engine frame = 14'9") long. Surface is covered with floor grating
 Motor rails (specify motor size)



800-831-0042 989-866-2381
www.morbark.com