


# MORBARK 2600 WOOD HOG

## BENEFITS


- Compact, easy-to-tow grinder from the leading manufacturer of industrial grade grinding equipment.
- Process brush, yard waste, and other mixed woody feedstocks into saleable products.
- Backed by a world class parts & service support team.
- Long lasting, durable machine that holds its value.
- Proven drive line protection system that protects against catastrophic damage from contaminants.
- Built in a quality-driven factory by highly experienced personnel.



**Morbark Integrated Control Systems**  
Automatically adjusts feed rates, monitor pressures and feed wheel position to maximize production and engine efficiency.



**HAMMERMILL**  
Laser-cut upturn rotor, factory balanced with forged hammers offer unsurpassed durability and smooth operation.



**FEED SYSTEM**  
Internal planetary drive with no chains and sprockets means lower maintenance, more torque and better durability.



**OPTIONS**  
Dual axles and extended discharge conveyor for loading open top trailers are available as an option.

## SPECIFICATIONS

Note: Specifications may vary with equipment options

02252010

### GENERAL

Length (transport).....33'8"  
Length (operating).....33'8"  
Height .....11'6"  
Width .....7' 10"  
Gross weight .....27,880 lbs.  
Axle weight.....23,720 lbs.  
Tongue weight .....4,160 lbs.  
Engine.....CAT, Cummins or John Deere  
Horsepower ..... 174 HP to 260 HP  
Fuel capacity (tank) ..... 90 gallons  
Hydraulic oil capacity..... 90 gallons  
Morbark Integrated Control Systems  
Dust Suppression system

### INFEED SYSTEM

20" x 57" infeed opening  
57"x9'7" live floor with 4-strand WDH 110 chain  
One 22" diameter top compression feed roll with internal drive

### HAMMERMILL AND GRATES

Hammermill system constructed of heavy duty 15-1/2" Equipped with twenty-two 1 1/4" thick forged steel heavy duty hammers with 1" spacers and twenty-two 2-1/16" wide double-edged replaceable hammerhead inserts and twenty-two rakers  
Two sections of 3/4" thick wear form steel heavy duty grates

### DISCHARGE SYSTEM

One hydraulically driven continuous belt conveyor  
Stacking height with standard conveyor 11'4"  
Stacking height with optional long conveyor 15' 8 1/2"

### OPTIONS

Magnetized end pulley with collecting slide tray for ferrous metal removal  
Variety of grates sizes available  
Long Conveyor  
Air compressor  
Break-away torque limiter



800-831-0042 989-866-2381  
www.morbark.com