

# MORBARK 4600XL TRACK WOOD HOG

## BENEFITS

- An aggressive, productive track grinder from the leading manufacturer of industrial-grade grinding equipment.
- Process clearing debris, yard waste, storm debris and other mixed woody feedstocks into saleable products.
- Backed by a world-class parts and service support team.
- Long-lasting, durable machine that holds its value.



**Morbark Integrated Control Systems**  
The ultimate diagnostic system; monitors hydraulic pressures, temperatures, clutch systems and engine efficiency while automatically adjusting to maximize performance.



**HAMMERMILL**  
Laser-cut upturn rotor, factory balanced with forged hammers offer unsurpassed durability and smooth operation.



**FEED SYSTEM**  
Internal planetary drive on feed wheel with no chains and sprockets means lower maintenance, more torque and better durability.



**TRACK AND DRIVE**  
325L Caterpillar undercarriage with 600mm double grouser pads with ground clearance of 20"

## SPECIFICATIONS

Note: Specifications may vary with equipment options

02012012

### GENERAL

Length (transport).....42' 6"  
Length (operating).....61' 10"  
Height ..... 11' 11"  
Width ..... 11' 11"  
Gross weight .....88,640 lbs.  
Engine.....CAT or Cummins  
Horsepower..... 800 HP to 1050 HP  
Fuel capacity (tank) .....340 gallons  
Hydraulic oil capacity.....267 gallons  
Morbark Intergrated Control Systems  
Hydraulically operated debris containment door  
Twenty four function radio remote control  
Dust suppression system

### INFEED SYSTEM

60" x 46" infeed opening  
9.3 cubic yard infeed hopper  
Variable speed infeed system consisting of one 33" diameter top compression feed roll with internal drive and a 14'6" long x 60-3/8" wide live floor equipped with four strands of WDH-120 chain in a staggered configuration and 4'7" long hydraulically folding infeed extension

### HAMMERMILL AND GRATES

36" diameter x 61 3/8" hammermill with 36" tip swing  
25 1/2" diameter rotors, (16) 1 3/8" thick rotor plates on 8 3/8" diameter rotor shaft with (2) 5 3/16" bearings, (8) 2" hammer retaining rods (30) 2" thick-balanced forged steel heavy-duty hammers equipped with (30) 3 1/16" wide double-edged replaceable hammerhead inserts and (18) rakers. Three sections of 1" thick wear form steel heavy-duty hexagon grates.

### DISCHARGE SYSTEM

Discharge system consisting of a hydraulically driven, horizontal 48" wide aggregate belly belt conveyor discharging onto a 36" wide stacking conveyor with hydraulic fold for transport  
Stacking height 16'2"

### OPTIONS

Variety of screen sizes available  
Hydraulic reversing fan  
Hydraulic rod puller  
Various hammer patterns  
11-HP air compressor  
Magnetized end pulley  
Dual bed chain drive system  
Externally adjustable torque limiter



800-831-0042 989-866-2381  
www.morbark.com