

D 86 Track Stump Grinder

Grind more, move less and get there faster with:

- Less repositioning on the stump with 19% wider boom swing than comparable models
- Powerful propulsion system with 4-speed ground travel and creep mode
- Access hard to reach areas with Long Boom Technology that maintains full boom arc swing regardless of cutting depth
- Hydraulically expandable rubber track undercarriage allows access through a 36" gate



LONG BOOM TECHNOLOGY
Maintains full boom arc swing regardless of cutting depth



WIRELESS REMOTE CONTROL
19-function radio remote control with 50' tethered back-up system



HYDROSTATIC DRIVE
3.3ci hydrostatic motor with 8cc functions gear pump, 16cc track drive gear pump and 5.4ci hydrostatic transmission



EXPANDABLE TRACK DRIVE SYSTEM
72" long x 9" wide, turf friendly, expandable track drive system



SPECIFICATIONS

Note: Specifications may vary with equipment options

07082010

GENERAL

Length	154" - 165"
Width	35" - 47"
Height	70"
Weight	5,760 lbs.
Engine	Kubota
Horsepower	84-99 HP
Fuel capacity	21-gallon
Hydraulic oil capacity	42-gallon
Boom arc swing	86"
Boom travel up	12"
Boom travel down	19"
Tracks	72" long x 9" wide
Primary drive	Hydrostatic
Secondary drive	Poly belt
Cutter wheel	1,250 RPM

EQUIPMENT HIGHLIGHTS

72" long x 9" wide expandable (35" to 47") rubber track undercarriage with 4.4 PSI ground pressure
86" Boom arc swing with Long Boom Technology and adjustable swing speed
19-Function wireless remote control operation with tethered back-up system controls the boom functions, travel, track expansion, throttle and emergency stop functions
Fully enclosed, liquid cooled, 4-cylinder diesel engine
Stationary engine platform maintains a low center of gravity and increases stability
2" x 4" x 1/4" thick tubular steel frame
Hydrostatic primary drive with belt final drive and electronic cutting system brake
Morthane Paint System: A chemically cured, electrostatically applied urethane coating with high gloss finish, built in UV protection, chip and chemical resistance and corrosion protection

ADDITIONAL FEATURES

Piloted flange cutter head bearings with 1-3/4" diameter 4140 hardened cutter shaft
Hydraulic tank inspection cover
Pre-plumbed for attachment of plow assembly
Choice of six cutting system options

OPTIONS

Hydraulic back-fill blade
Special color Morthane paint
Fold-away boom mounted deflect curtain assembly



800-831-0042 989-866-2381
www.morbark.com