

# MODEL HD-30 MULCH HOG

## OTHER

- Double door opening for huge access area to mill
- (2) 4 groove, 5V belts to the mill
- 2 groove, 5V belt to the hydraulic pump
- 2 usable edge, replaceable anvil
- Easily removed/rotated anvil for fast replacement
- Patent pending variable force, constant down pressure hydraulic system with feed control
- Hammermill rods can be configured to be removed from either side
- Stacking /discharge conveyor



## SPECIFICATIONS Note: Specifications may vary with equipment options

03052010

### GENERAL

Power .....200-300 HP electric motor  
 ..... 250-350 HP diesel motor  
 Length .....180'  
 Height .....76"  
 Width .....70"  
 Infeed Opening ..... 10" x 31"  
 Discharge Height.....5' to 15'  
 Drive System ..... belt & sheave drive, 8 groove  
 Hydraulic oil tank capacity..... 25-1/2 gallons  
 Bearings.....Dodge taper-lock piloted flange  
 Hammers.....(18) 2" wide fixed hammers with 3"  
 wide viper inserts

### OPTIONS

Outfeed Conveyor, consisting of:  
 9' level, 8' upright dual C188 drag chain conveyor that discharges at 6' 15' height  
 3/16" x 1-1/2" x 2-1/2" angle iron flites on 15" center  
 Constructed from 7 gauge steel  
 Hydraulic direct lock drive with chain speeds up to 70' per minute  
 Infeed vibrating conveyor: 20' long x 30" wide x 10" high straight sides. Conveyor formed of 3/8" panning and includes 10-HP electric drive  
 Infeed belt conveyor: 20' long x 30" wide x 10" high straight sides. Conveyor formed of 3/8" panning and includes smooth belt and hydraulic drive  
 Additional length by foot for vibrating conveyor

Additional length by foot for belt conveyor  
 Additional length by foot for outfeed conveyor  
 Hydraulic drive for infeed in lieu of electric (vibrating conveyor)  
 Direct coupled motor  
 Separate 25-HP motor to run hydraulic pump



800-831-0042 989-866-2381  
[www.morbark.com](http://www.morbark.com)